

SnowPlow Specifications

FOR MACHINES WEIGHING	FlexPlow™ 2,000-6,000 lbs.				UltraPlow™ 6,000-14,000 lbs.						AlphaPlow™ 14,000-30,000 lbs.	
												
Model Number	FX-5.0	FX-6.0	FX-7.0	FX-8.0	Ultra-72	Ultra-84	Ultra-96	Ultra-108	Ultra-120	Ultra-132	Alpha-10.0	Alpha-12.0
Blade Width	5'	6'	7'	8'	6'	7'	8'	9'	10'	11'	10'	12'
Blade Width at Full Angle	49.2"	59"	68.8"	78.6"	59"	68.8"	78.6"	88.5"	98.3"	114.6"	98.3"	118.0"
Blade Height	30"	30"	30"	30"	30"	30"	30"	30"	30"	30"	38"	38"
Weight (lbs.) (actual—not ship weight)	479	511	543	575	732	774	816	858	920	962	1,920	2,217
Moldboard Gauge	12 Ga.	12 Ga.	12 Ga.	12 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.
Trip Springs	2 Extension (4 Opt.)				4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	8 Ext	8 Ext
Wear Shoes	Yes	Yes	Yes	Yes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	N/A	N/A
Cutting Edge	1/2" x 6"				5/8" x 6"						3/4" x 8"	
Angle Rams	1-1/2" x 10" Chrome				1-1/2" x 13" Nitro Steel				2" x 13" Nitro Steel		2" x 13" D/A Nitro Steel*	
Vertical Ribs	6	6	6	6	6	6	6	6	8	8	8	10
Moldboard Radius	15"	15"	15"	15"	14"	14"	14"	14"	14"	14"	19"	19"
Full Down Pressure	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Floating / Full	
Spring Assist Down Pressure	Yes	Yes	Yes	Yes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	N/A	N/A
Universal Skid Steer Compatible	Standard				Standard						N/A	N/A
Cross Over Relief Valve	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Std.	Std.	Std.	Std.	Std.	Std.
SoftTouch™ Cutting Edge	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
UltraMAX HD Cylinder Kit	N/A	N/A	N/A	N/A	Opt.	Opt.	Opt.	Std.	Std.	Std.	N/A	N/A
High Carbon Curb Guards	N/A	N/A	N/A	N/A	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	N/A	N/A

* Double Acting Cylinder