

AlphaBlower Specifications

Introducing SnowWolf AlphaBlowers, aggressive and efficient snowblowers for hydraulic-drive wheel loaders and PTO-drive tractors. In another snow removal industry first, our new AlphaBlowers combine the best of a hydraulic drive with an aggressive open ribbon design time-tested for decades in the high mountain passes of Norway.




AlphaBlower™ 33-100-H

Hydraulic Flow: 40-50 GPM



AlphaBlower™ 33-100-P

PTO Power : 130-250 HP



AlphaBlower™ 36-106-P

PTO Power : 150-350 HP

Model Number	33-100-H	33-100-P	36-106-P
Overall Width at Drift Breakers (cm)	106.5" (270)	106.5" (270)	111" (282)
Center Cutting Height (cm)	44.0" (112)	44.0" (112)	48.0" (122)
Side Cutting Height (cm)	76.4" (194)	76.4" (194)	76.4" (194)
Impeller Diameter (cm)	32.7" (83)	32.7" (83)	35.4" (90)
Impeller Depth (cm)	11" (28)	11" (28)	13" (33)
Auger Diameter (cm)	35.8" (91)	35.8" (91)	37.4" (95)
Weight (kg)	4,304 lbs (1,956)*	3,650 lbs (1,659)	4,495 lbs (2,043)
Hardox 500 Reversible Cutting Edges (cm)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)
Hardox 500 Side Skids	Standard	Standard	Standard
Hardox Impeller Housing	Standard	Standard	Standard
Auto Reset Hydraulic Cut-out Clutch(es)	Standard (2)	Standard (2)	Standard (1)
HD Upper Wing Edges (Drift Breakers)	Standard	Standard	Standard
Screw Adjustable Gauge Wheels	Optional	Optional	Standard
Hydraulic Chute Rotation	Standard	Standard	Standard
Deluxe HD 4-flap Chute	Standard	Standard	Standard
Hydraulically Collapsible Chute	Optional	Optional	Standard
HD Truck Loading Chute	Optional	Optional	Optional
PTO Stub Shaft Diameter	N/A	1-¾"	1-¾"
PTO (RPM)	N/A	540** or 1,000	1,000
PTO Shaft Included	N/A	Standard	Standard
Recommended GPM (LPM)	40-50 (150-190)	N/A	N/A
Recommended PTO HP	N/A	130 - 250	150 - 350
To Fit Rear Mount PTO	N/A	Standard	Standard
To Fit Rear Mount PTO (towing position)	N/A	Standard	N/A
To Fit Front Mount PTO	N/A	Optional	Standard

* With Cat Fusion mount

** 540 RPM not currently stocked

